

LEGEND

EXISTING ITEMS - TO REMAIN UNLESS NOTED OTHERWISE.
EXISTING CMU BLOCK INFILL TO RECEIVE PAINT, COLOR TO BE SELECTED
NEW CMU BLOCK INFILL, PAINT, COLOR TO BE SELECTED
ORIGINAL SANDSTONE
CONCRETE SILLS, LINTELS, AND WATER TABLE
ASPHALT SHINGLES MATCH TO EXISTING
WOOD SIDING, PAINT COLOR TO BE SELECTED

GENERAL NOTES

- GENERAL NOTES, KEYNOTES, AND LEGEND ON THIS SHEET REFER TO THIS SHEET ONLY.
- 2. SEE MECHANICAL, ELECTRICAL, STRUCTURAL AND CIVIL DRAWINGS FOR ADDITIONAL INFORMATION.
- 3. ALL GUTTERS AND DOWNSPOUTS TO BE PREFINISHED.
- 4. SEE SHEET 10.10 AND 11.10 FOR DOOR AND WINDOW INFORMATION AND FINISHES.
- 5. METAL FLASHING TO BE SELECTED FROM THE MANUFACTURER'S STANDARD RANGE OF COLORS TO MATCH WINDOWS (SEE SHEET
- 11.10). 6. PROVIDE AND INSTALL KNOX BOX 36" A.F.F. FLUSH MOUNT TO STONE.
- COORDINATE EXACT LOCATION WITH FIRE DEPARTMENT. 7. SURROUNDING BUILDINGS NOT SHOWN FOR CLARITY, SEE THE SITE PLAN AND CIVIL DRAWINGS.

KEYNOTES

1 ELECTRICAL SERVICES, PAINT. 2 FOUNDATION, SEE STRUCTURAL DRAWINGS.

3 NOT USED.

- 4 PREFINISHED 6" X 4 1/2" RECTANGULAR GUTTER, SEE SPEC. 5 PREFINISHED 4 1/2" X 4 1/2" SQUARE DOWNSPOUT, SEE SPEC.
- 6 NOT USED.
- DEMO ALL EXISTING SHINGLE LAYERS ON SHED ROOF DOWN TO SUB-ROOFING. INSTALL 1/2" PLYWOOD SHEATHING, 15# BUILDING PAPER, ICE/WATER SHIELD, AND SHINGLES. PROVIDE PREFINISHED METAL DRIP EDGE, COLOR TO BE SELECTED.
- 8 NOT USED. PAINT EXISTING C.M.U. BLOCK INFILL, COLOR TO BE SELECTED.
- 10 NOT USED. 11 NOT USED.
- 12 NOT USED.
- REMOVE EXISTING FIRE ESCAPE AND ALL ASSOCIATED ATTACHMENTS, PLATFORMS, AND ANCHORS TO GRADE. GROUT HOLES IN MASONRY AS NEEDED WHERE FIRE ESCAPE WAS ANCHORED TO BUILDING. (15) INFILL WITH CMU AT LOCATION - SEE THE FLOOR PLANS, PAINT.
- 16 NOT USED.
- 17 NOT USED.
- (18) SEAL ROOF PENETRATION WATER TIGHT, SEE SHEET 1.20 AND MECHANICAL DRAWINGS.
- 19 NOT USED. 20 NOT USED.
- 21 NOT USED
- 22 NOT USED.
- PROVIDE PREFINISHED METAL FLASHING ALONG UPPER EDGES OF SHED ROOF WHERE SHINGLES MEET STONE FACADE. SAW-CUT STONE AND INSTALL FLASHING INTO STONE, PROVIDE CONTINUOUS SEALANT ALONG ENTIRE LENGTH OF TRIM - SEAL WATER TIGHT.

