


- A. INSTALL ALL PLUMBING PIPING WITHIN FRAMED WALLS OR ABOVE CEILINGS TIGHT TO OR WITHIN STRUCTURE UNLESS NOTED OTHERWISE. COORDINATE LOCATIONS WITH OTHER TRADES PRIOR TO INSTALLATION. PLAN OFFSETS AS REQ'D TO
- AVOID CONFLICTS WITH DUCTWORK AND/ OR STRUCTURE.
- C. FLOOR DRAIN LOCATIONS ARE SHOWN APPROXIMATE. CONFIRM ALL LOCATIONS WITH THE ARCHITECT PRIOR TO ROUGH-IN AND SET FINAL ELEVATION TO ACCOMMODATE SLOPING FLOORS.





- 2. APPROX MIN ROOF DRAIN INVERT IS 95.5-FT. SLEEVE FOUNDATION OR ROUTE UNDER FOOTINGS. SLOPE DRAINS 1/4-IN PER FT MIN. COORDINATE DEPTH AND
- OFFSET AND INSTALL INSULATED ROOF DRAIN LEADER DOWN WITHIN WALL
- INSTALL INSULATED OVERFLOW DRAIN DOWN FROM ABOVE AND EXTEND THRU
- THE EXTERIOR WALL TO DISCHARGE SPOUT HIGH-UP AT APPROX 11'-6" AFF. COORDINATE WITH THE GC.
- ABOVE. INSTALL STACK CLEAN-OUT AT THE BASE OF THE RISER.
- B. COMBINE SANITARY VENTS HIGH-UP AND EXTEND UP WITHIN WALL FRAMING
- 9. OFFSET AND EXTEND SANITARY VENT UP WITHIN WALL FRAMING ABOVE.
- 1. SEE PLUMBING ISOMETRICS FOR ADDITIONAL WASTE AND VENT SCOPE OF WORK
- 12. SEE LARGE SCALE PLAN FOR ADDITIONAL WASTE AND VENT SCOPE OF WORK IN



DRAIN WASTE & VENT