



ROCK SPRINGS, WYOMING 82901



-018

ATE

-27-2025

DRAWN BY

WILSON
CARPER

SK ID.

LEFT TITLE

FIRST FLOOR
FINISH PLAN

SHEET NUMBER

9.15



1. GENERAL NOTES AND LEGEND ON THIS SHEET REFER TO SHEETS 4.10 THROUGH 4.20 ONLY.
2. SEE THE INTERIOR ELEVATIONS, REFLECTED FINISH PLANS, AND SECTION C/D FOR THE SPECIFICATIONS AND CONDITIONS NOT SHOWN OR INDICATED ON THIS PLAN.
3. ALL FINISHES EXTEND FROM THE FLOOR TO THE CEILING OR STRUCTURE/ROOF DECK ABOVE UNLESS NOTED OTHERWISE.
4. PAINT FINISHES EXTEND TO KINKS/JOINTS OR DOORS AT HEAD/JAMB LOCATIONS. SEE THE KINK/JOINT AND DOOR DETAILS.
5. INSTALL TRANSITION STRIPS AT INTERSECTIONS OF DIFFERENT FINISHING MATERIALS. FINISHING MATERIALS SHOULD BE MATCHED APPROPRIATE TO ADJOINING FLOORING MATERIAL. SEE KEYNOTES FOR ADDITIONAL INFORMATION.
6. ALL INTERIOR HOLLOW METAL DOOR FRAMES AND VISION LITE TRANSOM DOORS AND HOLLOW METAL WINDOW FRAMES TO BE PAINTED. COLOR TO BE DETERMINED.
7. ALL PAINTED GYPSUM BOARD WALLS AND CEILING TO RECEIVE LEVEL 4 FINISH (TEXTURE ALL PRIMER AND PAINT PROJECTS WITH 1/4" SMOOTH BRUSH BACKS AND BACKS TO ACQUIRE A SUFFICIENT "TEXTURE". SPRAY-TEXTURE NOT TO BE USED IN THIS PROJECT).
8. ALL GYPSUM BOARD CEILINGS AND SPOFFS TO BE PAINT COLOR F1 UNLESS NOTED OTHERWISE.
9. ALL 10" OUTSIDE CORNERS (VERTICAL) TO BE SQUARE PUT. UNLESS NOTED OTHERWISE.
10. PAINT ALL INTERIOR EXPOSED STEEL STRUCTURAL ITEMS INCLUDING STAIR RAILING GUARD RAIL, AND COLUMNS UNLESS NOTED OTHERWISE. COLOR TO BE P4.
11. PROVIDE MOISTURE-RESISTANT GYPSUM BOARD ON THE WALLS IN THE FOLLOWING LOCATIONS TO 0'-0" ABOVE FINISH FLOOR:
WEST BEHIND REAR BATH DOORS 1022, 1023, 1024, 1025, 1109, WEST BEHIND SINKS 1116 (WEST BEHIND SINKS 1117, 1118, 1119, 1120, 1121, 1122, 1123, 1124, 1125, 1126, 1127, 1128, 1129, 1130, 1131, 1132, 1133, 1134, 1135, 1136, AND BEHIND PATTERN FOUNTAIN LITE N 014, 0101).
12. PROVIDE ABRUS-RESISTANT FINISHES ON THE FOLLOWING LOCATIONS TO 0'-0" ATGS: 1008, 1009, 1007, 1016, AND 1119.
ALL THE BASE AND OUTSIDE OF EXPOSED CORNERS TO RECEIVE TYPICAL JOLLY ATGS. ON DEPOSED EDGES, COLOR TO BE BRUSHED KINK FINISH.
13. ALL TILE NOSING ON STAIRS TO RECEIVE RONDEZ-STEP ATGS. COLOR TO BE BRUSHED KINK FINISH.
14. MECHANICAL AND ELECTRICAL EQUIPMENT HAS NOT BEEN SHOWN ON THIS PLAN FOR CLARITY. SEE THE REFERENCE PLANS AND MECHANICAL/ELECTRICAL DRAWINGS.
15. ALL EXTERIOR HOLLOW METAL DOORS AND FRAMES TO BE PAINTED COLOR TO BE SELECTED TO MATCH INTERIOR HOLLOW METAL FRAMES).
16. SEE INTERIOR ELEVATIONS FOR RFP-BIBS/CLASAS REINFORCED PANEL LOCATIONS NEAR RFP-BIBS IN OUTSIDE AREAS.
17. ALL MECHANICAL GRILLES/DIFFUSERS THAT ARE MOUNTED IN A REINFORCED AREAS ARE TO BE PAINTED THE SAME COLOR AS THE WALL.

	GYP /TAFE UNF OPEN STR ST SACT MSG GYP KB CONC P1 P2 P3 P4 CPT 1 CPT 2 RF	-UNFINISHED GYPSUM BOARD, TAPED (NO TEXTURE OR PAINT) -UNFINISHED -OPEN TO STRUCTURE ABOVE, NO FINISH -OPEN TO STRUCTURE ABOVE, DRYFALL PAINT ALL EXPOSED ITEMS EXCEPT DUCTWORK AND IT/ DATA ITEMS. COLOR: P4 -STONE INTERIOR VENEER FINISH: MONTANA ROCKWORKS - CHARCOAL LEDGE THIN VENEER, DRYSTACK -ACCOUSTICAL CEILING TILE: 24"X24" USG ORION 85, FB PROFILE, ACoustICAL PANELS IN USG FINELINE DXF GRD SYSTEM - SEE THE REFLECTED CEILING PLAN -WOOD SLAT FLOOR: ARMSTRONG - WOODWORKS GRILLE FORTE SOLID WOOD - RED OAK (RKO) ON POPLAR, 3/4" SLAT BTKENESS: 4 1/4" SLAT HEIGHT, 4 SLATS PER PANEL, ITEM CODE: 6324.06504GRK - SEE THE REFLECTED CEILING PLAN -GYPSUM BOARD PAINTED CEILING, SEE REFLECTED CEILING PLAN -RUBBER BASE: SOLID, HOMOGENEOUS RUBBER, MINIMUM THICKNESS OF .25" .25" HEIGHT, TARKETT - JOHNSONETTE - MILLIKNOCK MONUMENT PROFILE - 8.5 BLACK FEAT USE 4" HEIGHT RUBBER BASE OF SAME COLOR AT ALL CASEWORK, TOE KICKS, TYP. -SEALED CONCRETE: CLEAR COAT SEALANT, SMOOTH SURFACE, NO COLOR -PAINT, COLOR: ACRYLIC LATEX PAINT, E656HELL, COLOR TO BE S/N 7003 PURE WHITE -PAINT, ACCENT COLOR: ACRYLIC LATEX PAINT, E656HELL, COLOR TO BE S/N 7504 KEYSTONE GRAY -PAINT, ACCENT COLOR: ACRYLIC LATEX PAINT, E656HELL, COLOR TO BE S/N 9620 PRELUDE -PAINT, COLOR: ACRYLIC LATEX PAINT, E656HELL, COLOR TO BE S/N 7615 SEALSK -CARPET TILE: 18" X 36" MODULAR TILES, STAGGER INSTALL PATTERN, SHAN - CULTURA - CROSS HEMVEE TILE NATIVE 23105 -WALK OFF CARPET: 18" X 36" MODULAR TILES, ASHLAR INSTALL PATTERN, SHAN - ENTRYWAY CARPET TILE - SNIFT TILE ST414: TRCOT14500 -RUBBER FLOORING: EGOSURFACES ROLL - EGOPIT - TAKE ONE 1214 - 0.2MM THICKNESS, INSTALLED DIRECTLY OVER CONCRETE.
--	--	---

500 INSTALL TRANSITION STRIPS AT INTERSECTION OF DIFFERENT FLOORING MATERIALS: CONCRETE TO CARPET, LVT, SIZE AS APPROPRIATE FOR MATERIAL THICKNESS. SCHLUTER TRIM, RENO-RAMP PROFILE, IN THE FINISH SATIN ANODIZED ALUMINUM.

501 INSTALL TRANSITION STRIPS AT INTERSECTION OF DIFFERENT FLOORING MATERIALS: CARPET LVT TO RUBBER FLOORING, SIZE AS APPROPRIATE FOR MATERIAL THICKNESS. SCHLUTER TRIM, RENO-TX PROFILE, IN THE FINISH BRUSHED NICKEL, ANODIZED ALUMINUM.

502 INSTALL TRANSITION STRIPS AT INTERSECTION OF DIFFERENT FLOORING MATERIALS: PORCELAIN LVT TO CARPET LVT, SIZE AS APPROPRIATE FOR MATERIAL THICKNESS. SCHLUTER TRIM, RENO-TX PROFILE, IN THE FINISH BRUSHED NICKEL, ANODIZED ALUMINUM.

504 INSTALL TRANSITION STRIPS AT INTERSECTION OF DIFFERENT FLOORING MATERIALS: CARPET LVT TO LVT, SIZE AS APPROPRIATE FOR MATERIAL THICKNESS. SCHLUTER TRIM, VINPRO-F PROFILE, IN THE FINISH BRUSHED NICKEL, ANODIZED ALUMINUM.

505 INSTALL TRANSITION STRIPS AT INTERSECTION OF DIFFERENT FLOORING MATERIALS: PORCELAIN LVT TO LVT, SIZE AS APPROPRIATE FOR MATERIAL THICKNESS. SCHLUTER TRIM, RENO-V PROFILE, IN THE FINISH BRUSHED NICKEL, ANODIZED ALUMINUM.

506 INSTALL TRANSITION STRIPS AT INTERSECTION OF DIFFERENT FLOORING MATERIALS: PORCELAIN LVT TO RUBBER FLOORING, SIZE AS APPROPRIATE FOR MATERIAL THICKNESS. SCHLUTER TRIM, RENO-V PROFILE, IN THE FINISH BRUSHED NICKEL, ANODIZED ALUMINUM.

507 INSTALL TRANSITION STRIPS AT INTERSECTION OF DIFFERENT FLOORING MATERIALS: PORCELAIN LVT TO CONCRETE, SIZE AS APPROPRIATE FOR MATERIAL THICKNESS. SCHLUTER TRIM, RENO-RAMP PROFILE, IN THE FINISH BRUSHED NICKEL, ANODIZED ALUMINUM.

508 INSTALL SCHLUTER TRIM AT STAIR NOSINGS, SIZE AS APPROPRIATE FOR MATERIAL THICKNESS, ROUNDED, STEP PROFILE, IN THE FINISH BRUSHED NICKEL, ANODIZED ALUMINUM.

509 INSTALL SCHLUTER TRIM AT STAIR NOSINGS, SIZE AS APPROPRIATE FOR MATERIAL THICKNESS, ROUNDED, STEP PROFILE, IN THE FINISH BRUSHED NICKEL, ANODIZED ALUMINUM.

510 INSTALL SCHLUTER TRIM AT STAIR NOSINGS, SIZE AS APPROPRIATE FOR MATERIAL THICKNESS, ROUNDED, STEP PROFILE, IN THE FINISH BRUSHED NICKEL, ANODIZED ALUMINUM.

511 INSTALL SCHLUTER TRIM AT STAIR NOSINGS, SIZE AS APPROPRIATE FOR MATERIAL THICKNESS, ROUNDED, STEP PROFILE, IN THE FINISH BRUSHED NICKEL, ANODIZED ALUMINUM.

512 STAIR TREADS, RISERS, AND LANDINGS TO BE CPT 1.

513 STAIR RAILING, GUARDRAIL, AND ALL EXPOSED INTERIOR STEEL TO BE PAINTED IN THE COLOR P-4.

514 INSTALL ROLLER SHADES - SIGNATURE SERIES, ECHO 5% OPENNESS, COLOR: ROAD RAGE 493 B, FIELD VERIFY WINDOW SIZE.

515 INSTALL ROLLER SHADES - SIGNATURE SERIES, ECHO 5% OPENNESS, COLOR: ROAD RAGE 493 B, FIELD VERIFY WINDOW SIZE.

516 DENOTES ELEVATOR CAB FINISH.

517 INSTALL BUILDING PLAQUE SEE DETAIL 10/8-4.4 AND 4/4-1.

518 INSTALL TRANSITION STRIPS AT INTERSECTION OF RECESSED DOOR TRACK AND FLOORING TYPE: PORCELAIN LVT, SIZE AS APPROPRIATE FOR MATERIAL THICKNESS. SCHLUTER TRIM, RENO-RAMP PROFILE, IN THE FINISH SATIN ANODIZED ALUMINUM.

519 INSTALL TRANSITION STRIPS AT INTERSECTION OF RECESSED DOOR TRACK AND CARPET LVT, SIZE AS APPROPRIATE FOR MATERIAL THICKNESS. SCHLUTER TRIM, VINPRO-F PROFILE IN THE FINISH BRUSHED NICKEL, ANODIZED ALUMINUM.

520 INSTALL TRANSITION STRIPS AT INTERSECTION OF RECESSED DOOR TRACK AND CARPET LVT, SIZE AS APPROPRIATE FOR MATERIAL THICKNESS. SCHLUTER TRIM, VINPRO-F PROFILE IN THE FINISH BRUSHED NICKEL, ANODIZED ALUMINUM.

521 INSTALL TRANSITION STRIPS AT INTERSECTION OF RECESSED DOOR TRACK AND CARPET LVT, SIZE AS APPROPRIATE FOR MATERIAL THICKNESS. SCHLUTER TRIM, VINPRO-F PROFILE IN THE FINISH BRUSHED NICKEL, ANODIZED ALUMINUM.

522 INSTALL "EXIT" SIGN: SEE SIGNAGE LEGEND ON SHEET 4.26.

523 INSTALL "USE STAIR" SIGN: SEE SIGNAGE LEGEND ON SHEET 4.26.

524 INSTALL TRANSITION STRIPS AT INTERSECTION OF DIFFERENT FLOOR MATERIALS: RUBBER FLOORING TO LVT, SIZE AS APPROPRIATE FOR MATERIAL THICKNESS. SCHLUTER TRIM, VINPRO-T PROFILE IN THE FINISH BRUSHED NICKEL, ANODIZED ALUMINUM.

530 INSTALL "MAXIMUM OCCUPANT" SIGN: SEE SIGNAGE LEGEND ON SHEET 4.26.

531 QUARTZ TOP: CORIANI QUARTZ FORTORO®

532 GRANITE COUNTERTOP: ARIZONA TILE, 'BUZZONITE'

533 PROVIDE NAIL FINISH AND PAINT TO EXTEND 1'-0" ABOVE CEILING HEIGHT IN ROOMS WITH MOOD SALT CELINGS, ENTIRE ROOM.

535 INSTALL "MAIN LEVEL EVACUATION PLAN" SIGN: SEE SIGNAGE LEGEND ON SHEET 4.26.