GENERAL NOTES


- EXT'G CONDITIONS ARE BASED ON AVAILABLE INFORMATION. PRIOR TO SUBMITTING A BID, THE CONTRACTOR SHALL VISIT THE SITE TO VERIFY ALL CONDITIONS AND DIMENSIONS. NO EXTRAS WILL BE GIVEN FOR FAILURE TO INVESTIGATE.
- 2. MEANS AND METHODS ARE THE RESPONSIBILITY OF THE CONTRACTOR. INCLUDE FOR A COMPLETE INSTALLATION WITHOUT ADDITIONAL COST TO THE OWNER.
- 3. FIELD ORGANIZE AND INSTALL ALL EQUIPMENT, DUCTWORK, PIPING, CONDUIT, ETC FOR MAXIMUM CLEARANCE AND MAINTENANCE ACCESSIBILITY. (ALL TRADES)
- 4. EXISTING PIPING, DUCTWORK AND EQUIPMENT SHOWN LIGHT. NEW PIPING, DUCTWORK AND EQUIPMENT SHOWN BOLD.
- 5. EXISTING PIPING, DUCTWORK AND EQUIPMENT TO REMAIN OR THAT WHICH IS NOTED TO BE REUSED SHALL BE PROTECTED FROM DAMAGE.

6. MOUNT ALL EQUIPMENT HIGH AND TIGHT TO STRUCTURE.

KEY NOTES

1/4" = 1'-0" 01

- INSTALL NEW CONDENSATE LINES FOR EACH NEW FAN COIL PER MFGR'S INSTRUCTIONS. EXTEND AND COMBINE LINES AS REQ'D AND MAKE CONNECTION THE THE EXISTING CONDENSATE LINE AS INDICATED.
- 2. EXTEND NEW SANITARY WASTE, VENT AND DOMESTIC WATER LINES DOWN TO THIS LOCATION FOR CONNECTION TO THIS NEW SINK LOCATION. ALL LINES SHALL BE LOCATED IN THE WALL CAVITY AND HIDDEN FROM VIEW.
- 3. RELOCATE EXISTING FIRE PROTECTION MAIN LINE AND LATERAL BRANCH LINES PER RENOVATIONS SHOWN. RELOCATE FIRE PROTECTION HEADS PER NEW WALL LOCATIONS. ADD ADDITIONAL HEADS TO PROVIDE ADEQUATE PROTECTION PER NFPA-13 REQUIREMENTS. FIRE SPRINKLER ENGINEER BY G.C. COORDINATE WITH ALL TRADES PRIOR TO INSTALLATION. RE-CERTIFY THE SYSTEM AS REQ'D.





BASEMENT FLOOR ALTERNATE #6 WASTE & VENT RENOVATION

BASEMENT FLOOR PLAN - ALTERNATE #6 WASTE & VENT RENOVATION